

DECLARATION OF PERFORMANCE N. CPR-DE1/90506411

- 1) Unique identification code of the product-type: Rasco 1K PMBC classic S
- 2) Intended uses: Polymer modified bitumen thick coating for waterproofing
- 3) Manufacturer: Rasco Bitumentechnik GmbH, Otto-von-Guericke-Ring 11, 65205 Wiesbaden, www.bitumentechnik.de
- 4) Systems of AVCP:System 3System 3 (for reaction to fire)
- 5) Harmonized standards: EN 15814:2011+A2:2014

Notified bodies:

The notified body Materialprüfungsamt Nordrhein-Westfalen, ID-No. 0432, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The notified body Materialprüfungsamt Nordrhein-Westfalen, ID-No. . 0432 carried out the assessment of the performance (reaction to fire) on the basis of testing on samples taken by the manufacturer.

Essential characteristics	Performances
Watertightness	Class W2A
Crack bridging ability	Class CB2
Water resistance	no coloration of the water, no debonding from inlay
Flexibility at low temperature	no cracks
Dimensional stability at high temperature	no sliding or draining down
Reaction to fire	Class E
Resistance to compression	Class C2A
Dangerous substances	npd
Durability of water tightness and reaction to fire	passed

6) Performances declared:



The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Holger Fleischmann – Plant manager

Augustdorf, 26.04.2017

lind

DoP in Pdf format are available on the Rasco website.

Revision 2 notes: Product unchanged. Adjustment of product codifiaction.



CE 0432	Rasco Bitumentechnik GmbH Otto-von-Guericke-Ring 11 - 65205 Wiesbaden www.bitumentechnik.de	
15		
CPR-DE1/90506411 EN 15814:2011+A2:2014		
Rasco 1K PMBC classic S		
Polymer modified bitumen thick coating for waterproofing		
Watertightness		Class W2A
Crack bridging ability		Class CB2
Water resistance		no coloration of the water, no debonding from inlay
Flexibility at low temperature		no cracks
Dimensional stability at high temperature		no sliding or draining down
Reaction to fire		Class E
Resistance to compression		Class C2A
Dangerous substances		npd
Durability of water tightness and reaction to fire		passed

Note:

Rasco supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.