

DECLARATION OF PERFORMANCE N. CPR-DE1/90506421

Unique identification code of the product-type:
Rasco 1K PMBC low shrinkage S

2) Intended uses:

Polymer modified bitumen thick coating for waterproofing

3) Manufacturer:

Rasco Bitumentechnik GmbH, Otto-von-Guericke-Ring 11, 65205 Wiesbaden, www.bitumentechnik.de

4) Systems of AVCP:

System 3

System 3 (for reaction to fire)

5) Harmonized standards: EN 15814:2011+A2:2014

Notified bodies:

The notified body Technische Universität München, Materialprüfungsamt für das Bauwesen, Abteilung Baustoffe, ID-No. 1211, performed the identification of the product type on the basis of a type test, a type calculation of product description documents, and issued the type test report.

The notified body Materialprüfungsamt Nordrhein-Westfalen, ID-No. 0432 carried out the assessment of the performance (reaction to fire) on the basis of testing on samples taken by the manufacturer.

6) Performances declared:

Essential characteristics	Performances
Watertightness	Class W2A
Crack bridging ability	Class CB2
Water resistance	no coloration of the water, no debonding from inlay
Flexibility at low temperature	no cracks
Dimensional stability at high temperature	no sliding or draining down
Reaction to fire	Class E
Resistance to compression	Class C2A
Dangerous substances	NPD
Durability of water tightness and reaction to fire	passed



The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Holger Fleischmann – Plant manager

Augustdorf, 02.07.2018

DoP in Pdf format are available on the Rasco website.

Revision 2 notes: Update of the notified bodies.





Otto-von-Guericke-Ring 11 - 65205 Wiesbaden www.bitumentechnik.de

17

CPR-DE1/90506421 EN 15814:2011+A2:2014 Rasco 1K PMBC low shrinkage S

Polymer modified bitumen thick coating for waterproofing

Watertightness Class W2A Crack bridging ability Class CB2

Water resistance no coloration of the water,

no debonding from inlay

Flexibility at low temperature no cracks

Dimensional stability at high temperature no sliding or draining down

Reaction to fire Class E

Resistance to compression Class C2A

Dangerous substances NPD

Durability of water tightness and reaction to fire passed

Note:

Rasco supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.