Safety Data Sheet

RASCO Bitumen Voranstrich Konzentrat

Safety Data Sheet dated: 09/03/2022 - version 2



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: RASCO Bitumen Voranstrich Konzentrat

Trade code: 9050733 UFI: SU20-V0J9-5009-N70Q

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: One -component bituminous coating

Uses advised against: Data not available

1.3. Details of the supplier of the safety data sheet

Company: Rasco Bitumentechnik GmbH, Otto-von-Guericke-Ring 11, D-65205 Wiesbaden, Germany

phone: +49-05237 608 0 - fax: +49-05237 608 210 (office hours)

Responsible: rasco@bitumentechnik.de 1.4. Emergency telephone number

Poison emergency call Berlin +4930 30686700 (Advice in German and English)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Skin Sens. 1A May cause an allergic skin reaction.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) n. 1272/2008 (CLP)

Pictograms and Signal Words



Warning

Hazard statements:

H317 May cause an allergic skin reaction.

Precautionary statements:

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves/clothing and eye/face protection.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with applicable regulations.

Contains:

2-octyl-2H-isothiazol-3-one

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration \geq 0.1%.

Other Hazards: No other hazards

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

Date 3/29/2022 Production Name RASCO Bitumen Voranstrich Konzentrat Page n. 1 of 12

SECTION 3: Composition/information on ingredients

3.1. Substances

Not Relevant

3.2. Mixtures

Mixture identification: RASCO Bitumen Voranstrich Konzentrat

Hazardous components within the meaning of the CLP regulation and related classification:

| Concentration (% w/w) | Name | Ident. Numb. | Classification | Registration Number |
|-----------------------|--|--|--|-----------------------|
| ≥1 - <2.5 % | 1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N dimethyl-, N-C8- 18(even numbered) acyl derivs., | CAS:97862-59-4 - EC:931-296-8 | Eye Dam. 1, H318 Aquatic Chronic 3, H412 | 01-2119488533-30-xxxx |
| | hydroxides, inner salts | | Specific Concentration Limits: 4% ≤ C < 10%: Eye Irrit. 2 H319 C ≥ 10%: Eye Dam. 1 H318 | |
| ≥0.0015 - <0.005 % | ethylene glycol | CAS:107-21-1 EC:203-473-3 Index:603-027- 00-1 | Acute Tox. 4, H302; STOT RE 2, H373 | 01-2119456816-28-xxxx |
| ≥0.0015 - <0.005 % | 2-octyl-2H-isothiazol-3-one | CAS:26530-20-1 EC:247-761-7 Index:613-112- 00-5 | Acute Tox. 2, H330 Acute Tox. 3, H311 Acute Tox. 3, H301 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Corrosive to the respiratory tract., M-Chronic:100, M-Acute:100 | |
| | | | Specific Concentration Limits: C ≥ 0.0015%: Skin Sens. 1A H317 | , |
| | | | Acute Toxicity Estimate: ATE - Oral: 125mg/kg bw ATE - Dermal: 311mg/kg bw | |
| <0.0015 % | free crystalline silica (Ø <10 μ) | CAS:14808-60-7 EC:238-878-4 | STOT RE 1, H372 | |

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Not available

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Date 3/29/2022 Production Name RASCO Bitumen Voranstrich Konzentrat Page n. 2 of 12

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

List of components with OEL value

| Component | OEL Type | Country | Ceiling | Long Term mg/m3 | Long Term ppm | Short Term mg/m3 | Short Term ppm | Behaviour | Note |
|-----------------|-------------|---------|---------|-----------------------|---------------------|------------------------|----------------------|-----------|---|
| ethylene glycol | National | SWEDEN | | 25 | 10 | 50 | 20 | | SWEDEN, Short-term value, 15 minutes average value |
| | National | FINLAND | | 50 | 20 | 100 | 40 | | FINLAND, hud |
| | National | NORWAY | | 52 | 20 | 104 | 40 | | NORWAY, H5 |
| | National | SWEDEN | | 25 | 10 | 50 | 20 | | SWEDEN, Short-term value, 15 minutes average value |
| | EU | None | | 52 | 20 | 104 | 40 | | Skin |
| | National | NORWAY | | 10 | 10 | 20 | 20 | | |
| | ACGIH | None | С | | | 100 | | | (H), A4 - URT and eye irr |
| | National | NORWAY | | 26 | | 52 | | | |
| | DFG | GERMANY | С | | | 52 | 20 | | |
| | ACGIH | | | | 25 | 10 | 50 | | A4 - Not Classifiable as a Human Carcinogen;upper |

| | | | | | | | | | respirator, tract irritation |
|--|------------------|-------------------|---|----------|----|------|------|------------|--|
| | Nationa | SWEDEN | | 25 | 10 | | | | |
| | Nationa | FRANCE | | 52 | 20 | 104 | 40 | | |
| | Nationa | SPAIN | | 52 | 20 | 104 | 40 | | |
| | Nationa | GREECE | | 125 | 50 | 125 | 50 | | |
| | Nationa | DENMARK | | 26 | 10 | | | | |
| | Nationa | DENMARK | | 10 | 10 | | | | |
| | National | FINLAND | | 50 | 20 | 100 | 40 | | |
| | National | PORTUGAL | | 52 | 20 | 104 | 40 | | |
| | Nationa | NORWAY | | 52 | 20 | 104 | 40 | | |
| | NDS | POLAND | | 15 | | | | | |
| | | POLAND | | | | 50 | | | |
| | | PORTUGAL | С | | | 100 | | | |
| | CHE | SWITZERLAND | | | | 52 | 20 | | |
| | NDS | NETHERLANDS | | 52 | | 104 | | | |
| | NDS | NETHERLANDS | | 10 | | 104 | | | |
| | | GERMANY | | 26 | 10 | 101 | | | |
| | National | | | 50 | 10 | | | | |
| | Nacional | REPUBLIC | | 30 | | | | | |
| | Nationa | HUNGARY | | 52 | | 104 | | | |
| | Nationa | SLOVAKIA | | 52 | 20 | | | | |
| | Nationa | SLOVENIA | | 52 | 20 | 104 | 40 | | |
| | Nationa | UNITED KINGDOM | | 10 | 20 | 104 | 40 | | |
| | Nationa | UNITED KINGDOM | | 10 | 20 | 30 | 40 | | |
| | Malaysi a OEL | MALAYSIA | С | | | 100 | 39.4 | | |
| | Nationa | ESTONIA | | 52 | 20 | 104 | 40 | | |
| | Nationa | l LATVIA | | 52 | 20 | 104 | 40 | | |
| | Nationa | CZECH REPUBLIC | С | | | 100 | | | |
| | National | SLOVAKIA | С | | | 104 | | | |
| | | CROATIA | C | 52 | 20 | 104 | 40 | | |
| | EU | CROATIA | | 52 52 | 20 | 104 | | Indicativo | Descibility of cignificant |
| | LU | | | 32 | 20 | 104 | 40 | Indicative | Possibility of significant uptake through the skin |
| | Nationa | UNITED KINGDOM | | 52 | 20 | 104 | 40 | | |
| | Nationa | BULGARIA | | 52 | 20 | 104 | 40 | | |
| | Nationa | ROMANIA | | 52 | 20 | 104 | 40 | | |
| | TUR | TURKEY | | 52 | 20 | 104 | 40 | | |
| | Nationa | LITHUANIA | | 25 | 10 | 50 | 20 | | |
| 2-octyl-2H-isothiazol-3- one | DFG | GERMANY | С | | | 54 | 10 | | |
| | Nationa | GERMANY | | 0.05 | | | | | |
| | CHE | SWITZERLAND | | | | 0.1 | | | |
| | | SLOVENIA | | 0.05 | | 0.05 | | | |
| | DFG | GERMANY | С | - | | 0.1 | | | |
| | | SLOVENIA | | 0.05 | | 0.1 | | | |
| free crystalline silica (Ø $<10~\mu$) | | SWEDEN | | 0.100 | | | | | SWEDEN, respirable aerosol |
| | Nationa | NORWAY | | 0.100 | | | | | K: Chemicals to be treated as carcinogenic. |
| | | | | | | | | | |

Date 3/29/2022 Production Name RASCO Bitumen Voranstrich Konzentrat Page n. 4 of 12

| NDS POLAND | 2.000 | | frakcja wdychalna |
|----------------------------|-------|-------|--|
| NDS POLAND | 0.300 | | frakcja respirabilna |
| National DENMARK | 0.3 | 0.600 | DENMARK, inhalable aerosol |
| National DENMARK | 0.100 | 0.200 | DENMARK, respirable aerosol |
| ACGIH None | 0.025 | | (R), A2 - Pulm fibrosis, lung cancer |
| EU None | 0.025 | | A2 (R) - Pulm fibrosis, lung cancer |
| National AUSTRIA | 0.150 | | A* |
| ACGIH | 0.025 | | A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis |
| National SWEDEN | 0.1 | | |
| National FRANCE | 0.1 | | |
| National SPAIN | 0.05 | | |
| National DENMARK | 0.3 | | |
| National DENMARK | 0.1 | | |
| National FINLAND | 0.05 | | |
| National PORTUGAL | 0.025 | | |
| National NORWAY | 0.3 | 0.9 | |
| National NORWAY | 0.1 | 0.9 | |
| National BELGIUM | 0.1 | | |
| NDS POLAND | 0.1 | | |
| NDS NETHERLANDS | 0.075 | | |
| National CZECH REPUBLIC | 0.1 | | |
| National HUNGARY | 0.15 | | |
| Malaysi MALAYSIA a OEL | 0.1 | | 0.1 mg/m3 TWA (respirable dust) |
| National ESTONIA | 0.1 | | |
| National SLOVAKIA | 0.1 | 0.5 | |
| National SLOVENIA | 0.1 | | |
| National BULGARIA | 0.07 | | |
| National ROMANIA | 0.1 | | |
| National LITHUANIA | 0.1 | | |
| National CROATIA | 0.1 | | |
| National ITALY | 0.100 | | |
| (51.5) | | | |

Predicted No Effect Concentration (PNEC) values

| caicte | a no Enece con | | ic) values | | |
|---|---|-----------------|-----------------|------------------------|----------------------------------|
| Compon | ent | CAS-No. | PNEC Limit | Exposure Route | Exposure Frequency Remark |
| amino-N- (carboxy dimethyl numbere | aminium, 3- - methyl)-N,N -, N-C8-18(even d) acyl derivs., es, inner salts | 97862-59-4 | 0.00135 mg/l | Marine water | |
| | | | 0.0135 mg/l | Fresh Water | |
| | | | 0.1 mg/kg | Marine water sediments | |
| | | | 1 mg/kg | Freshwater sediments | |
| | | | 0.8 mg/kg | Soil | |
| | | | 3000 mg/l | Microorganisms in | |
| Date | 3/29/2022 | Production Name | RASCO | Bitumen Voranstrich Ko | onzentrat |

sewage treatments

ethylene glycol 107-21-1

10 mg/l Fresh Water

1 mg/l Marine water

1.53 mg/kg Soil

37 mg/kg Freshwater

sediments

10 mg/l Intermittent release

199.5 mg/l Microorganisms in

sewage treatments

3.7 mg/kg Marine water

sediments

Derived No Effect Level. (DNEL)

| Component | CAS-No. | Worker Worke Industr Profes y ional | | Exposure Route | Exposure Frequency Remark |
|---|------------|---|--------------|------------------|-----------------------------|
| 1-Propanaminium, 3- amino-N- (carboxymethyl)-N,N dimethyl-, N-C8-18(even numbered) acyl derivs., hydroxides, inner salts | 97862-59-4 | 44 mg/m3 | | Human Inhalation | Long Term, systemic effects |
| | | 12.5 mg/kg | 7.5 mg/kg | Human Dermal | Long Term, systemic effects |
| | | | 7.5 mg/kg | Human Oral | Long Term (repeated) |
| ethylene glycol | 107-21-1 | 106 mg/kg | 53 mg/kg | Human Dermal | Long Term, systemic effects |
| | | | 53 mg/kg | Human Oral | Long Term, systemic effects |
| | | 35 mg/m3 | 7 mg/m3 | Human Inhalation | Long Term, local effects |

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to appropriate EN standards, like EN 136, 140, 143, 149, 14387 for information on selection and use of appropriate respiratory protection equipment.

Hygienic and Technical measures

Not available

Appropriate engineering controls:

Not available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Appearance: paste Color: Dark brown

Date 3/29/2022 Production Name RASCO Bitumen Voranstrich Konzentrat Page n. 6 of 12

Odour: Characteristic Odour threshold:

Melting point / freezing point: Not available Initial boiling point and boiling range: Not available

Flammability: Not available

Upper/lower flammability or explosive limits: Not available

Flash point: Not available

Auto-ignition temperature: Not available Decomposition temperature: Not available

pH: 10.00

Viscosity: 250,000.00 cPs Kinematic viscosity: Not available Solubility in water: dispersible Solubility in oil: Not available

Partition coefficient (n-octanol/water): Not available

Vapour pressure: Not available Relative density: 1.12 g/cm3 Vapour density: Not available **Particle characteristics:** Particle size: Not available

9.2. Other information

Miscibility: Not available Conductivity: Not available Explosive properties: === Solid/gas flammability: == No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological information of the mixture:

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation Not classified

Based on available data, the classification criteria are not met

c) serious eye damage/irritation Not classified

Based on available data, the classification criteria are not met

The product is classified: Skin Sens. 1A(H317) d) respiratory or skin sensitisation

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

Date 3/29/2022 **Production Name** RASCO Bitumen Voranstrich Konzentrat Page n. 7 of 12 i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

Not classified j) aspiration hazard

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

1-Propanaminium, 3amino-N-

a) acute toxicity

LD50 Oral Rat = 2335 mg/kg

(carboxymethyl)-N,N dimethyl-, N-C8-18(even numbered) acyl derivs., hydroxides, inner salts

LD50 Skin Rat > 2000 mg/kg

i) STOT-repeated

exposure

NOAEL Oral Rat = 300 mg/kg

ethylene glycol a) acute toxicity LC50 Inhalation Rat > 2.50000 mg/l 6h LD50 Skin Rat > 3500.00000 mg/kg

2-octyl-2H-isothiazol-3-

one

a) acute toxicity

ATE - Oral: 125 mg/kg bw

ATE - Dermal: 311 mg/kg bw LD50 Oral Rat = 318 mg/kg LD50 Skin Rabbit = 311 mg/kg

LC50 Inhalation Dust Rat = 0.58 mg/l 4h

free crystalline silica (Ø a) acute toxicity

 $<10 \mu$)

LD50 Oral Rat = 500 mg/kg

11.2 Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >=0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards

Based on available data, the classification criteria are not met

List of components with eco-toxicological properties

| Component | Ident. Numb. | Ecotox Infos |
|--|---|---|
| 1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N dimethyl-, N C8-18(even numbered) acyl derivs., hydroxides, inner salts | CAS: 97862-59-4 - - EINECS: 931-296-8 | a) Aquatic acute toxicity: LC50 Fish = 1.1 mg/L 96 |
| | | a) Aquatic acute toxicity: EC50 Daphnia = 1.9 mg/L 48 |
| | | a) Aquatic acute toxicity: NOEC Algae = 0.6 mg/L 72 |
| | | d) Terrestrial toxicity: NOEC > 846 mg/kg - 14 d |
| | | e) Plant toxicity: NOEC = 84.4 mg/kg - 17 d |
| ethylene glycol | CAS: 107-21-1 - EINECS: 203-473-3 - INDEX: 603-027- 00-1 | a) Aquatic acute toxicity: EC50 Daphnia > 100 mg/L 48 |
| | | a) Aquatic acute toxicity: EC50 Algae > 100 mg/L 96 |

a) Aquatic acute toxicity: LC50 Fish > 100 mg/L 96 b) Aquatic chronic toxicity: NOEC Fish > 100 mg/L - 7 d

- b) Aquatic chronic toxicity: NOEC Daphnia > 100 mg/L 7 d
- b) Aquatic chronic toxicity: NOEC Algae > 100 mg/L 72
- a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 41000 mg/L S IUCLID
- a) Aquatic acute toxicity: LC50 Fish Oncorhynchus mykiss 14 mL/L 96h EP.
- a) Aquatic acute toxicity: LC50 Fish Lepomis macrochirus = 27540 mg/L 9
- PA
- a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = $40761 \text{ mg/L} \ \text{S}$ IUCLID
- a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 40000 mg/L 96h EPA $\,$
- a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata = 16000 mg/L 96h IUCLID
- a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 46300 mg/L 48 IUCLID
- a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata $6500 \, \text{mg/L}$ 96h IUCLID

2-octyl-2H-isothiazol-3-one

CAS: 26530-20-1 -EINECS: 247-761-7 - INDEX: 613-112-

00-5

a) Aquatic acute toxicity: EC50 Daphnia = 0.42 mg/L 48

a) Aquatic acute toxicity: EC50 Algae = 0.084 mg/L 72
 a) Aquatic acute toxicity: LC50 Fish = 0.036 mg/L 96
 a) Aquatic acute toxicity: LC50 Fish = 0.18 mg/L 96

b) Aquatic chronic toxicity: NOEC Daphnia = 0.002 mg/L - 21 db) Aquatic chronic toxicity: NOEC Fish = 0.022 mg/L - 28 db) Aquatic chronic toxicity: NOEC Algae = 0.004 mg/L 72

12.2. Persistence and degradability

Not available

12.3. Bioaccumulative potential

Not available

12.4. Mobility in soil

Not available

12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration \geq 0.1%.

12.6 Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7 Other adverse effects

Not available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Hazardous waste: Yes Disposal considerations:

Do not allow to enter drains or watercourses.

Date 3/29/2022 Production Name RASCO Bitumen Voranstrich Konzentrat Page n. 9 of 12

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

Not Applicable

14.2. UN proper shipping name

Not Applicable

14.3. Transport hazard class(es)

Not Applicable

14.4. Packing group

Not Applicable

14.5. Environmental hazards

Not Applicable

14.6. Special precautions for user

Not Applicable

Road and Rail (ADR-RID):

ADR-Hazard identification number: NA

Not Applicable

Air (IATA):

Not Applicable

Sea (IMDG):

Not Applicable

14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

Bitumen based product. When transported at elevated temperature, the product must be considered dangerous for all modes of transport.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC): N.A. g/l

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) n. 2020/878

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP) Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

.... 10 da. (20) ... 2020, 2202 (.... 20 da.)

Provisions related to directive EU 2012/18 (Seveso III):

Not available

Date 3/29/2022 Production Name RASCO Bitumen Voranstrich Konzentrat Page n. 10 of 12

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 75

SVHC Substances:

No data available

German Water Hazard Class (WGK)

1

Code

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Description

| H302 | Harmful if swallowed. | | | | |
|------------|---|-----------------------------------|--|--|--|
| H317 | May cause an allergic skin reaction. | | | | |
| H318 | Causes serious eye damage. | | | | |
| H319 | Causes serious eye irritation. | | | | |
| H372 | Causes damage to organs through prolonged or repeated exposure. | | | | |
| H373 | May cause damage to organs through prolonged or repeated exposure if swallowed. | | | | |
| H412 | Harmful to aquatic life with long lasting eff | ects. | | | |
| Code | Hazard class and hazard category | Description | | | |
| 3.1/4/Oral | Acute Tox. 4 | Acute toxicity (oral), Category 4 | | | |

| Code | nazaro ciass ano nazaro category | Description |
|------------|----------------------------------|--|
| 3.1/4/Oral | Acute Tox. 4 | Acute toxicity (oral), Category 4 |
| 3.3/1 | Eye Dam. 1 | Serious eye damage, Category 1 |
| 3.3/2 | Eye Irrit. 2 | Eye irritation, Category 2 |
| 3.4.2/1A | Skin Sens. 1A | Skin Sensitisation, Category 1A |
| 3.9/1 | STOT RE 1 | Specific target organ toxicity — repeated exposure, Category ${\bf 1}$ |
| 3.9/2 | STOT RE 2 | Specific target organ toxicity — repeated exposure, Category 2 |
| 4.1/C3 | Aquatic Chronic 3 | Chronic (long term) aquatic hazard, category 3 |

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

| Classification according to Regulation | Classification procedure |
|--|--------------------------|
| (EC) Nr. 1272/2008 | |
| 3.4.2/1A | Calculation method |

If appropriate, specific provisions in relation to possible training for workers are mentioned in section 2. Any training related to safety in the workplace must in any case refer to a risk assessment that must be carried out by a company safety officer taking into account the specific operating and environmental conditions in which the products are used.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center
CE: European Community

CLP: Classification, Labeling, Packaging.

Date 3/29/2022 Production Name RASCO Bitumen Voranstrich Konzentrat Page n. 11 of 12

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand COV: Volatile Organic Compound CSA: Chemical Safety Assessment CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive DSD: Dangerous Substances Directive EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

* Sheet model entirely changed in compliance to regulatory update.

Date 3/29/2022 Production Name RASCO Bitumen Voranstrich Konzentrat Page n. 12 of 12