

Rascorol Fleece 120

PP-based reinforcement fabric for embedding in Rascorol pro

For embedding and reinforcing Rascorol pro on critical, e.g. crack-endangered substrates and for maintaining the required layer thicknesses.



PRODUCT FEATURES

TECHNICAL DATA

Recommended for critical substratesFrost-free at least 24 months shelf-life	Width	1,050 mm
	Thickness	0.7 mm
	Color	white
	Material	100% PP
	Weight	≥ 120 g/m²

DELIVERY UNITS

50 rm / 52,5 m² / roll

GENERAL NOTES


In case of sealing or maintenance work the relevant standards and guidelines must be followed.


APPLICATION

- Rascorol Fleece 120 hast to be cut to the relevant length and embedded fully and firmly using suitable tools into the first fresh layer of Rascorol pro.
- · Following fleece sheets have to be applied with a minimum of 5 cm overlapping at the edges.
- · Then Rascorol pro is applied in the required layer thickness.
- · If work is interrupted, make sure that before application of the second layer of Rascorol pro, Rascorol Fleece 120 has not been moistened with dew or rain.
- · Rascorol Fleece 120 should be embedded in the centre of the completed, two-layered Rascorol pro and should not protrude out of the coating in any place.

SPECIAL NOTES

- Rascorol Fleece 120 is to be protected from sun, rain and frost before and during application until Rascorol pro is completely dry.
- Information relating to Rascorol pro and other product ranges can be found on our website http://www.rasco-bitumen.com







Note: The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in effect at the time of the Rasco product installation. For the most up-to-date TDS and warranty information, please visit our website at www.rasco-bitumen.com. Any alterations to the wording or requirements contained in or derived from this TDS shall void all related Rasco warranties.

Issue 01: First issue of this product TDS. When this version is updated it will lose its validity.