

Rasco Bitumen Trowelling Compound

Solvent-free, stable trowelling compound based on a bituminous emulsion. For repair work, waterproofing and trowelling work on roofs and roof windows. For the temporary sealing of joints and cracks

It can be applied to fibre cement sheet, bituminous membranes and sheeting as well as all suitable bituminous substrates, metals, plastics and all known suitable substrates.



PRODUCT FEATURES

- Solvent-free and environmentally friendly
- Ready to use
- UV-resistant
- Clean, easy and fast use
- Good elasticity
- Applicable by trowel and stable
- Resistant to frost and de-icing salts
- Frost-free at least 12 months shelf-life

TECHNICAL DATA

Consumption*	1.0 kg/m ² per mm coat thickness
Density	approx. 1.0 kg/l
Workable after**	24 hours
Working and drying temperature***	+5°C to +30°C

* The consumption rates shown are minimum values. These may increase according to the manner of application.

** These times may vary greatly, depending on humidity, temperature, coating thickness and substrate. Times are based on the standard climate of + 23 °C and 50 % relative humidity.

*** Temperature: component, installation and ambient temperature.

DELIVERY UNITS

10 kg bucket / 44 buckets / pallet | pallet weight: approx. 480 kg

5 kg bucket / 60 buckets / pallet | pallet weight: approx. 350 kg

1 kg bucket | 6 buckets / carton | 64 cartons / pallet | pallet weight approx. 425 kg

GENERAL NOTES

In case of sealing or maintenance work the relevant standards and guidelines must be followed.

SUBSTRATE PREPARATION

- The substrate must be sufficiently dry, level, stable, frost-protected, clean and without traces of oil, grease, tar, honeycombing, cracks, dust, dirt, residue mortar or other potential contaminants.

APPLICATION

Registered office: Otto-von-Guericke-Ring 11, 65205 Wiesbaden, Germany

Administration and production site: Imkerweg 32b, 32832 Augustdorf, Germany

Phone: +49 5237 608-0 - Fax: +49 5237 608-210 - email: rasco@bitumentchnik.de - www.rasco-bitumen.com

APPLICATION

- Rasco Bitumen Trowelling Compound is ready-to-use and can be applied straight out of the bucket using a trowel, smoothing or notched trowel to the prepared surface.
-

SPECIAL NOTES

- Protect the newly applied material from rain, frost and strong sun light until completely dry.
- Further information regarding Rasco systemic products may be found on our website <http://www.rasco-bitumen.com/>.
- Please note the Safety Data Sheet (accessible at <http://www.rasco-bitumen.com/>)

Note: The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in effect at the time of the Rasco product installation. For the most up-to-date TDS and warranty information, please visit our website at www.rasco-bitumen.com. Any alterations to the wording or requirements contained in or derived from this TDS shall void all related Rasco warranties.

Issue 04: This document has been updated with respect to resistance to frost and de-icing salts. When this version is updated it will lose its validity.