

Rasco Bitumen Primer SF

Solvent-free, fast-drying primer based on bituminous emulsion for substrate preparation before application of roofing membranes and sheeting

It can be applied to roofing areas, cellar walls, foundation slabs, balconies, underground garages and patios, prior application to bituminous roofing membranes and sheeting as well as all known and suitable mineral substrates.



PRODUCT FEATURES

- Solvent-free and environmentally friendly
- Ready to use
- Applicable with a pump/spray, roll or brush
- Suitable for use inside and outside
- Rapid drying
- Frost-free at least 12 months shelf-life

TECHNICAL DATA

Consumption*	0.15-0.20 l/m ²
Density	approx. 1.0 kg/l
Workable after**	15 minutes
Working and drying temperature***	+5°C to +30°C

* The consumption rates shown are minimum values. These may increase according to the manner of application.

** These times may vary greatly, depending on humidity, temperature, coating thickness and substrate. Times are based on the standard climate of + 23 °C and 50 % relative humidity.

*** Temperature: component, installation and ambient temperature.

DELIVERY UNITS

25 l canister | 24 canisters / pallet | pallet weight approx. 650 kg

10 l canister | 60 canisters / pallet | pallet weight approx. 650 kg

5 l canister | 96 canisters / pallet | pallet weight approx. 550 kg

GENERAL NOTES

In case of sealing or maintenance work the relevant standards and guidelines must be followed.

SUBSTRATE PREPARATION

- The substrate must be sufficiently dry, level, stable, frost-protected, clean and without traces of oil, grease, tar, honeycombing, cracks, dust, dirt, residue mortar or other potential contaminants.

APPLICATION

- **Rasco Bitumen Primer SF** is ready to use and applicable with a wide brush, brush, roller or suitable spraying

APPLICATION

technique evenly to the prepared substrate.

SPECIAL NOTES

- Protect the newly applied primer from rain, frost and strong sun light until completely dry.
- Further information regarding **Rasco systemic products** may be found on our website <http://www.rasco-bitumen.com/>.
- Please note the Safety Data Sheet (accessible at <http://www.rasco-bitumen.com/>)

Note: The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in effect at the time of the Rasco product installation. For the most up-to-date TDS and warranty information, please visit our website at www.rasco-bitumen.com. Any alterations to the wording or requirements contained in or derived from this TDS shall void all related Rasco warranties.

Issue 03: This document has been updated with respect to smaller editorial changes. When this version is updated it will lose its validity.